

## SERIES: **mono** ■ Single-stage Tensioners

**IN STOCK FOR QUICK DELIVERY**



### LATEST TECHNOLOGY

- Latest seal technology
- High cycle life
- Optimised load to weight ratio
- Integrated system with TensionPro pumps and hoses

### SAFE AND RELIABLE

- CE marked
- Over-stroke protection
- Max stroke indicator
- Pressure Test Certification
- Full colour operating and safety manual

### OPTIONS AND FEATURES

- Special threads
- Special load requirements
- Twin or single port
- Protective handle
- Special bridge for tight clearance
- Swivel connections
- Cycle counter
- Gear drive nut run-down
- Spring piston return
- Misalignment compensation
- ARMOURMAX anti-corrosion, anti-wear

**mono** series single-stage tensioners are versatile and reliable hydraulic bolt tensioners suitable for high load and tight space applications with limited overhead clearance. Optimised for use on **wind turbines** they have been designed for long-life, low-maintenance use, and are suitable for use on single bolts, or grouped together for multiple tightening of bolted joints. **single** tensioners are extensively used for slewing rings, power-gen applications, structural and all critical bolting.

### PROCESS IMPROVEMENT

**mono** Hydraulic Tensioners are designed for **speed**. Fast spring piston retract, geared nut run-down and spring located sockets, improve process time on each tensioning operation. High cycle life, over-stroke protection and the latest seal technology ensure **low maintenance** operation to keep projects on schedule.

Bolt Thread Size		Maximum Tensioner Load		Tool Height	Tool OD
T		F		H	A
inch	Metric	tonf	kN	mm	mm
1	M24	29.1	290	100	85
1 1/8	M27	38.1	380	105	90
-	M30	46.8	466	110	100
1 1/4	M33	57.2	570	115	110
1 3/8	M36	68.0	678	120	118
1 1/2	M39	81.3	810	125	124
1 5/8	M42	93.3	927	135	130
1 3/4	M45	108.8	1082	140	145
1 7/8	M48	122.7	1223	145	150
2	M52	146.0	1455	150	160
2 1/4	M56	168.1	1675	155	170
-	M60	195.7	1950	160	178
2 1/2	M64	225.3	2245	165	185

### SAFETY AND SPEED

Optional durable handle intergrated over the hydraulic connection for easy handling and positioning of the tool, protects the hose and inlet connection from unnecessary loading - benefiting the operator with an extra layer of safety.

